

# Battery powered magnetic watermeter for district metering of potable water

6500W

# Main

Range of product	Flow	
Product or component type	Magnetic flowmeter transmitter	
Device application	To measure the flow of pressure for liquid, gas, steam	
Market segment	Water	
Product specific application	Raw water Irrigation Water distribution network Water abstraction Pump control	
Device composition	liner in thermoplastic electrode in hastelloy electrode in stainless steel	

# Complementary

Tube diameter	25.4609.6 mm	
Measurement accuracy	+/- 0.2 % of reading with IMT65W	
Electrical conductivity	20 μS/cm	
Housing material	Stainless steel	
Mounting support	Flange conforming to EN 1092-1 Flange conforming to ASME B16.5 Flange conforming to JIS	

# **Environment**

5 1 1 115 11		
Product certifications	OIML R49	
	MID MI-001	
	ACS	
	DVGW	
	NSF	
	UBA	
	WRAS	



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

#### Environmental Data explained >

How we assess product sustainability >

☑ Environmental footprint	
Total lifecycle Carbon footprint	488
Environmental Disclosure	Product Environmental Profile

### **Use Better**

<b>⊗</b> Materials and Substances	
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Not compliant
REACh Regulation	REACh Declaration

### **Use Again**

○ Repack and remanufacture	
End of life manual availability	No need of specific recycling operations
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins