

Pressure transmitter, Pressure, absolute, accuracy of ±0.05%

IAP10S

Main

Range of Product	Pressure	
Product or Component Type	Pressure transmitter	
Type of Measurement	Absolute	

Complementary

turndown	400:1
Response Time	100 ms
mounting type	Direct connect Low profile Biplanar
Kit composition	Mounting bracket
Display Type	LCD display
Measurement accuracy	+/- 0.05 % of reading
Maximum pressure	6000 psi 414 bar
drift	+/- 0.03 % of measuring range per year, for 10 years
communication protocol	FOUNDATION fieldbus HART

Environment

IP67
NEMA 4X
FM CSA ATEX IEC-EX EAC INMETRO
TÜV Rheinland (SIL3) NEPSI NACE MR01-03

Packing Units

Unit Type of Package 1	PCE	
Nbr. of units in pkg.	1	

Contractual warranty

Warranty 5 years

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

☑ Environmental footprint	
Carbon footprint (kg CO2 eq, Total Life cycle)	107
Environmental Disclosure	Product Environmental Profile

Use Better

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Not compliant
SCIP Number	F5618823-9da4-420b-92fb-18cbfdc5a7c9
REACh Regulation	REACh Declaration
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Use Again

○ Repack and remanufacture	
Circularity Profile	End of Life Information
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.