

Pneumatic valve control, Valve Positioner, input 0.2 to 1 bar, ATEX

SRP981

Main

Range of Product	Valve Positioners
Product or Component Type	Valve positioner
Market Segment	Process industry

Complementary

Housing material	Aluminium alloy	
Input pressure	1.46 bar 2090 psi	
Maximum hysteresis	0.3 %	
Linearity	< 1 % of the travel span	
Pneumatic operation	Single acting Double acting	
Operating angle	30120 °	

Environment

Ambient Air Temperature for Operation	-40176 °F (-4080 °C) -4080 °C (-40176 °F)
IP Degree of Protection	IP54
Product certifications	ATFX

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

☑ Environmental footprint		
Carbon footprint (kg CO2 eq, Total Life cycle)	66	
Environmental Disclosure	Product Environmental Profile	

Use Better

Materials and Substances	
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant with Exemptions
REACh Regulation	REACh Declaration
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Use Again

○ Repack and remanufacture	
Circularity Profile	End of Life Information
Take-back	No
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.