

Loop-powered transmitter with 4-20 mA and HART digital outputs for contacting conductivity sensors.

876CR

Main

Range of Product	Process Liquid Analytical	
Product or Component Type	Transmitter	
Device Application	To measure conductivity To measure resistivity	
Market Segment	Paper and pulp Chemical Food and beverage Pharmaceutical Water and waste water	

Complementary

Terminal type	Display with keypad
Communication port protocol HART, 420 mA	

Environment

Product Certifications	CSA	
	FM	
	ATEX	
	IECEx	
	NEPSI	
	EAC	

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

∅ Environmental footprint		
Carbon footprint (kg CO2 eq, Total Life cycle)	343	
Environmental Disclosure	Product Environmental Profile	

Use Better

Materials and Substances	
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant with Exemptions
REACh Regulation	REACh Declaration
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Use Again

○ Repack and remanufacture		
Circularity Profile	End of Life Information	
Take-back	No	